



HSM V-Press 1160

HSM V-Press 1160 vertical baling press

With a maximum bale weight of 550 kg, strong pressing power and an absolutely high efficiency level, the HSM V-Press 1160 is the top-model of the HSM V-Press series.

Technical data

Order number:	6044114	Bale length x Bale width x Bale height:	1200 x 1200 x 1100 mm
EAN	4026631080330	Bale weight:	550 kg
Pressing power:	594 kN	Method of loading:	manual
Specific pressing power:	45 N/cm ²	Width x Depth x Height:	1780 x 1388 x 2985 mm
Driving power:	4 kW	Weight:	2300 kg
Voltage / Frequency:	400 V / 50 Hz	Related product line:	V-Press
Cycle time when idling vacío:	25 s	Type of consumables:	Wire, Pre-looped wire
Volume throughput in idle operation (theor.):	13,75 m ³ /h	Press material:	Plastic film, Mixed paper, Cardboard, Punch waste/residue
Loading height:	1115 mm		
Loading aperture width x height:	1195 x 650 mm		

Product information



To fill the press, the upper half of the doors is swung to the right



Hand wheel door lock - Easy to handle thanks to counter-rotating thread for quick opening and closing



The HSM V-Presses are highly energy efficient thanks to the rapid stroke technology. This saves time and money



Compresses cardboard and film

Suitable for cardboard as well as film.



Automatic start

Automatic start of the pressing process after closing the door.



Economical

Optimised bale dimensions and bale weights for efficient storage, transport and direct commercialisation.




Graphic-capable display

Convenient membrane keypad with text display, which shows the current status of the machine.



HSM TCS

HSM TCS (TorsionControlSystem) for monitoring press ram movement.



Strapping

Strapping with wire - optional tape station available for strapping with polyester tape or wire according to requirements.



www.tuev-sued.de/ps-zert



www.hsm.eu

HSM®