



HSM V-Press 504



HSM V-Press 504 vertical baling press

The entry-level model HSM V-Press 504 allows for the eco-nomical disposal of your packaging waste.

Technical data

Order number:	6151151	Loading aperture width x height:	700 x 470 mm
EAN	4026631074421	Bale length x Bale width x Bale height:	700 x 500 x 600 mm
Pressing power:	40 kN	Bale weight:	60 kg
Specific pressing power:	11,2 N/cm ²	Width x Depth x Height:	1020 x 812 x 1922 mm
Driving power:	1,1 kW	Weight:	290 kg
Voltage / Frequency:	230 V / 50 Hz	Related product line:	V-Press
Cycle time when idling vacío:	27 s	Type of consumables:	Strapping tape
Volume throughput in idle operation (theor.):	3,75 m ³ /h	Press material:	Plastic film, Mixed paper, Cardboard
Loading height:	661 mm		

Product information



Bale removal and transport with discharge trolley



HSM TCS (Torsion Control System) for monitoring press ram movement



Modern microprocessor controller with membrane keypad and text display

HSM®



Compresses cardboard and film

Suitable for cardboard as well as film.



Automatic start

Automatic start of the pressing process after closing the door.



Optimized pressing

Massive press ram and extremely robust press plate guidance.



Double door

To fill the press, the upper half of the doors is swung to the right.



Bell-crank lever

Bell-crank lever for quick and safe opening of the door.



Strapping

Manual bale strapping with continuous polyester tape.



Made in Germany



cost effective



simple operation



95% volume reduction



www.tuev-sued.de/ps-zert



www.hsm.eu

HSM®