



HSM V-Press 860 TimeSave

HSM V-Press 860 TimeSave vertical baling press

In addition to the well-known advantages of the V-Press series, the HSM V-Press 860 TimeSave has a decisive added-value factor: signficant savings in time with less staff needed for the task. Thanks to the time-saving lifting/tilting device, it only takes a few seconds to load the HSM V-Press 860 TimeSave using a collection cart.

Technical data

| Order number: | 6155304A | Bale weight: | 430 kg |
|---|-------------------------|-------------------------|--|
| EAN | 4026631075343 | Method of loading: | Automatic lifting/tilting system, wire mesh cart |
| Pressing power: | 594 kN | | system, wire mesn cart |
| Specific pressing power: | 63.46 N/cm ² | Width x Depth x Height: | 2202 x 3584 x 3004 mm |
| specific pressing power. | 03,401476111 | Weight: | 3680 kg |
| Driving power: | 7,0 kW (4+3 kW) | | |
| Voltage / Frequency: | 400 V / 50 Hz | Related product line: | V-Press |
| | | Type of consumables: | Quick link wire |
| Volume throughput in idle operation (theor.): | 26,25 m³/h | Press material: | Mixed paper, Cardboard |
| Bale length x Bale width x Bale height: | 1200 x 780 x 1200 mm | | |

Product information







Saves up to 1.5 h per bale compared to other vertical baling presses with automatic loading. Each cart is emptied within 12 seconds

Saves up to 5.0 h per bale compared to other vertical baling presses with manual loading

Convenient and particularly fast loading via hydraulic lifting/tilting device





Economical

Optimised bale dimensions and bale weights for efficient storage, transport and direct commercialisation.



Automatic start

Automatic start of the pressing process after closing the door.



Economical, fast and silent

The HSM V-Presses are highly energy efficient thanks to the specially developed rapid stroke technology. This saves time and money.



Graphic-capable display

Convenient membrane keypad with text display, which shows the current status of the machine.



HSM TCS

HSM TCS (Torsion Control System) for monitoring press ram movement.



Strapping

Manual bale strapping with Quick-link wire.



















www.tuev-sued.de/ps-zert

